NSN 5930-01-307-4473

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-307-4473

| Thread Class: |
|---|
| 2a |
| Body Style: |
| Bushing mounted |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 1.360 inches |
| Overall Width: |
| 0.314 inches |
| Bushing Length: |
| 0.300 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.270 inches |
| Body Height: |
| 0.450 inches |
| Case Material: |
| Plastic |
| Actuator Diameter: |
| 0.117 inches |
| Actuator Height: |
| 0.455 inches |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 6.000 amperes resistive dc and 3.000 amperes resistive ac |

Precious Material And Location:

Contact and terminal surfaces silver

NSN 5930-01-307-4473Push Switch - Page 2 of 2



| Inread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0