

View Online at <https://aerobasegroup.com/nsn/5930-01-307-5928>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.290 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-30.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

10 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug and turret

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0