## NSN 5930-01-308-1492



Thermostatic Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-308-1492 **Thread Class:** 2a single threaded stud **Hazardous Locations/environmental Protection:** Dustproof **Overall Height:** 0.937 inches **Body Height:** 0.376 inches **Overall Diameter:** 0.630 inches **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** Between 201.0 degrees fahrenheit and 300.0 degrees fahrenheit **Mounting Method:** Threaded stud Thready Qty Per Inch (tpi): 32 single threaded stud **Contact Action Stimulus:** Increase **Thread Size:** 0.138 inches single threaded stud **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Quick disconnect, male **Contact Load Current Rating:** 10.0 amperes resistive load second voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 220.00 actuation point degrees fahrenheit and 250.00 actuation point degrees fahrenheit and 20.00 differential point degrees fahrenheit and 100.00 differential point degrees fahrenheit **Contact Voltage Rating In Volts:** 240.0 ac at sea level second voltage Media For Which Designed:

Gas or liquid

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

Style Designator:

Disc

## NSN 5930-01-308-1492

Thermostatic Switch - Page 2 of 2



Th	read	1.5	eries	Desi	anato	r.
	ıı cav	a o	כו וכס	DESI	unato	ι.

Unc single threaded stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0