

View Online at <https://aerobasegroup.com/nsn/5930-01-308-4044>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

2.830 inches

Outside Diameter:

0.438 inches single connection

Overall Diameter:

0.710 inches

Pressure Switch Type:

Absolute

Width Across Flats:

1.000 inches

Operating Temperature Rating:

Between -67.0 degrees fahrenheit and 176.0 degrees fahrenheit

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

50.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage and 1.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

17.50 actuation point pounds per square inch absolute and 15.50 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Swivel nut, flared, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0