NSN 5930-01-308-4045

Thermostatic Switch - Page 1 of 2

Distance Between Mounting Facility Centers:

Overall Length: 0.970 inches

0.125 inchesBody Length:0.750 inches

0.250 inches

Mounting Slot Width:

Overall Diameter:



View Online at https://aerobasegroup.com/nsn/5930-01-308-4045

| 0.750 inches | | | | | |
|---|--|--|--|--|--|
| Tempurature Sensing Element Type: | | | | | |
| Internal sensor | | | | | |
| Operating Tempurature Rating: | | | | | |
| Between -65.0 degrees celsius and 150.0 degrees celsius | | | | | |
| Mounting Method: | | | | | |
| Bracket and slot | | | | | |
| Features Provided: | | | | | |
| Hermetically sealed case | | | | | |
| Contact Action Stimulus: | | | | | |
| Increase | | | | | |
| Mounting Facility Pattern: | | | | | |
| Two position in-line | | | | | |
| Nonpile-up Contact Arrangement: | | | | | |
| 1 pole, single throw, normally closed, momentary action | | | | | |
| Terminal Type: | | | | | |
| Tab, solder lug | | | | | |
| Contact Load Current Rating: | | | | | |
| 1.0 amperes resistive load first voltage | | | | | |
| Contact Adjustability: | | | | | |
| Actuation point not adjustable | | | | | |
| Contact Stimulus Rating: | | | | | |
| 176.00 actuation point degrees fahrenheit | | | | | |
| Contact Voltage Rating In Volts: | | | | | |
| 28.0 dc at sea level second voltage | | | | | |
| Media For Which Designed: | | | | | |
| Gas or liquid | | | | | |
| Precious Material And Location: | | | | | |
| Contacts platinum and contacts iridium | | | | | |
| Precious Material: | | | | | |
| Platinum and iridium | | | | | |
| Style Designator: | | | | | |
| Cylindrical | | | | | |

NSN 5930-01-308-4045

Thermostatic Switch - Page 2 of 2



| | | | | - |
|-----|----|-----|-----|-----|
| C I | 20 | lŧ. | l i | fe: |
| J. | 16 | | _, | ıc. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0