## NSN 5930-01-308-5087

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-308-5087

| view Offiline at https://aerobasegroup.com/hist//0000-01-000-000/ |
|---|
| Thread Class:   |
| 2a  |
| Body Style:   |
| Bushing mounted   |
| Overall Length:   |
| 0.500 inches  |
| Overall Height:   |
| 1.357 inches  |
| Overall Width:  |
| 0.260 inches  |
| Bushing Length:   |
| 0.344 inches  |
| Body Length:  |
| 0.500 inches  |
| Body Width:   |
| 0.260 inches  |
| Body Height:  |
| 0.639 inches  |
| Actuator Diameter:  |
| 0.200 inches  |
| Actuator Height:  |
| 0.218 inches  |
| Actuator Color:   |
| Black single actuator   |
| Maximum Voltage Rating In Volts:                                  |
| 125.0 ac and 28.0 dc  |
| End Application:  |
| 1520-01-106-9519 helicopter, attack                               |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Threaded bushing  |
| Thready Qty Per Inch (tpi):                                       |
| 40  |
| Thread Size:  |
| 0.250 inches  |
| Nonpile-up Contact Arrangement:                                   |
| 1 pole, double throw, one position momentary single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:             |
| 6.000 amperes resistive dc and 6.000 amperes resistive ac         |

**Precious Material And Location:** 

Contacts silver

## NSN 5930-01-308-5087

Push Switch - Page 2 of 2



| Thread Series Designator:   |
|-----------------------------|
| Uns                         |
| Terminal Type And Quantity: |
| 3 tab, solder lug           |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |

**Fiig:** A053a0