NSN 5930-01-308-5416

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-308-5416

Overall Length:
2.756 inches
Overall Height:
1.900 inches
Overall Width:
1.960 inches
Unthreaded Mounting Hole Diameter:
0.188 inches single mounting facility
Distance Between Mounting Facility Centers:
1.188 inches single mounting facility
Individual Section Quantity:
2
Operating Tempurature Range:
-20.0/+70.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob and cam actuated
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Cam Actuated Switch Contact Arrangement:
1 pole, single throw, double make, both positions maintained each switch each section in-line
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Screw
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
20.0 amperes resistive load lowest ac voltage rating at sea level
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
In-line, cam actuated
Shelf Life:
N/a

NSN 5930-01-308-5416Rotary Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A052b0