

View Online at <https://aerobasegroup.com/nsn/5930-01-308-9287>

Inside Diameter:

0.125 inches single connection

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

4.210 inches

Overall Height:

8.940 inches

Body Diameter:

7.750 inches

Unthreaded Mounting Hole Diameter:

Between 0.276 inches and 0.296 inches

Distance Between Mounting Facility Centers:

8.250 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 110.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Type:

Internal actuation point hex nut

Contact Voltage Rating In Volts:

110.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Special Features:

Switch actuates idependently on the decrease pressure of 1.9 inches of water and on increaseng preasure of 2.5 inches of water

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0