NSN 5930-01-308-9292

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-308-9292

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Corrosion resistant and fungus resistant

Overall Length:

Between 3.440 inches and 3.620 inches

Overall Height:

Between 2.470 inches and 2.530 inches

Overall Width:

Between 2.280 inches and 2.340 inches

Individual Section Quantity:

3

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

3 each section periphery

Mounting Facility Circle Radius:

1.155 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks each section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

NSN 5930-01-308-9292

Rotary Switch - Page 2 of 2



Sty	عا	D	26	ia	n	a	ŧ٥	r	
JLY	ı	יש	ငၥ	щ		а	ιv	ш	

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0