## NSN 5930-01-308-9292

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-308-9292

#### **Thread Class:**

2b single mounting facility

### Hazardous Locations/environmental Protection:

Corrosion resistant and fungus resistant

## **Overall Length:**

Between 3.440 inches and 3.620 inches

#### **Overall Height:**

Between 2.470 inches and 2.530 inches

#### **Overall Width:**

Between 2.280 inches and 2.340 inches

## Individual Section Quantity:

3

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 each section periphery

#### **Throw Quantity:**

3 each section periphery

## Mounting Facility Circle Radius:

1.155 inches single mounting facility

#### Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

### **Features Provided:**

Actuator knob

### Thready Qty Per Inch (tpi):

24 single mounting facility

#### Thread Size:

0.190 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

120.0 ac at sea level

#### Mounting Facility Pattern:

Four position circular single mounting facility

#### Switch Actuator Indexing Position Quantity:

3 single actuator

#### **Terminal Type:**

Tab w/screw

#### **Contact Switching Action:**

Makes before breaks each section periphery

#### Switch Actuator Positioning Increment:

90.0 degrees single actuator

## **Contact Load Current Rating:**

15.0 amperes resistive load ac at sea level

# NSN 5930-01-308-9292

Rotary Switch - Page 2 of 2

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

