NSN 5930-01-309-2376

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-309-2376
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Shock proof
Overall Length:
3.520 inches
Overall Height:
1.740 inches
Overall Width:
2.500 inches
Individual Section Quantity:
1
Knob Manufacturer Code:
27192
Knob Manufacturer Part Number:
53-1160
Longest Horizontal Distance Between Mounting Centers:
1.620 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.164 inches single mounting facility
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes single section periphery

45.0 degrees single actuator

Switch Actuator Positioning Increment:

NSN 5930-01-309-2376

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

750.0 milliamperes inductive load highest ac voltage rating at sea level

Special Features:

Legend plate reads run/stop in both center and clockwise positions

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0