NSN 5930-01-309-2377

Rotary Switch - Page 1 of 2

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Thread Class:

Thread Length:

Corrosion resistant

Overall Length:

3.703 inches

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-01-309-2377

Overall Diameter: 1.875 inches **Individual Section Quantity:** 4 **Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number:** An3220-3 **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section periphery **Throw Quantity:** 7 each section periphery **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.469 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 7 single actuator **Terminal Type:** Screw **Contact Switching Action:** Breaks before makes each section periphery **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed-adjustable stops single actuator

NSN 5930-01-309-2377

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level and 2.0 amperes lamp load dc at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0