

View Online at <https://aerobasegroup.com/nsn/5930-01-309-2379>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.937 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.281 inches single actuator

Overall Diameter:

1.062 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3:00 o'clock

End Application:

6625-01-016-5966 gain phase meter; ticonderoga class cg (47), virginia class cgn (41), spruance class dd (963), general purpose electronic test equipment gpete, los angeles class ssn (688), kidd class ddg, seawolf class ssn

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

4 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Special Features:

Weapon system essential

Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0