

View Online at <https://aerobasegroup.com/nsn/5930-01-309-2385>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

0.780 inches

Overall Height:

0.562 inches

Overall Width:

0.562 inches

Body Diameter:

0.562 inches

Bushing Length:

0.260 inches

Body Length:

0.197 inches

Case Material:

Metal

Actuator Diameter:

0.343 inches

Actuator Height:

0.125 inches

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Specification Data:

81349-mil-s-8805/110 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0