## NSN 5930-01-309-4074

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-309-4074

| Body Style:   |
|---|
| Bushing mount   |
| Overall Length:   |
| 0.500 inches  |
| Overall Height:   |
| 1.108 inches  |
| Overall Width:  |
| 0.395 inches  |
| Bushing Length:   |
| 0.280 inches  |
| Body Length:  |
| 0.500 inches  |
| Body Width:   |
| 0.270 inches  |
| Actuator Style:   |
| Round   |
| Actuator Diameter:  |
| 0.105 inches  |
| Actuator Height:  |
| 0.270 inches  |
| Actuator Position-action Relationship:  |
| Up position momentary and down position maintained and center position maintained |
| Maximum Voltage Rating In Volts:  |
| 20.0 ac and 20.0 dc   |
| Mounting Surface To Terminal End Distance:  |
| 0.550 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Threaded bushing  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit                   |
| Contact Load Current Rating At Maximum Rated Voltage:                             |
| 20.000 milliamperes resistive dc and 20.000 milliamperes resistive ac             |
| Special Features:   |
| Unthreaded bushing; printed circuit board mounted                                 |
| Precious Material And Location:   |
| Contact and terminal surfaces gold  |
| Terminal Type And Quantity:   |
| 3 printed circuit   |
| Shelf Life:   |

N/a

## **NSN 5930-01-309-4074** Toggle Switch - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV  | еа  | SU  | ıre: |

Demilitarization:

No

Fiig:

A053a0