

View Online at <https://aerobasegroup.com/nsn/5930-01-309-6753>

Hazardous Locations/environmental Protection:

Weathertight

Overall Length:

9.060 inches

Overall Height:

3.720 inches

Overall Width:

4.220 inches

Mounting Slot Width:

0.250 inches

Body Length:

4.220 inches

Distance Between Mounting Facility Centers:

2.750 inches

Pressure Switch Type:

Differential

Mounting Method:

Flange and slot

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

400.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.50/+12.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0