Pressure Switch - Page 1 of 2



Vi 309-6753

Plessule Switch - Page 1 01 2
View Online at https://aerobasegroup.com/nsn/5930-01-3
Hazardous Locations/environmental Protection:
Weathertight
Overall Length:
9.060 inches
Overall Height:
3.720 inches
Overall Width:
4.220 inches
Mounting Slot Width:
0.250 inches
Body Length:
4.220 inches
Distance Between Mounting Facility Centers:
2.750 inches
Pressure Switch Type:
Differential
Mounting Method:
Flange and slot
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
400.00 pounds per square inch
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
5.0 amperes resistive load second voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+0.50/+12.00 actuation point pounds per square inch
Contact Adjustment Type:
Internal actuation point hex nut
Contact Voltage Rating In Volts:
30.0 dc at sea level second voltage
Modia For Which Designed:

Media For Which Designed:

Gas or liquid

## NSN 5930-01-309-6753

Pressure Switch - Page 2 of 2

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

