NSN 5930-01-309-8644

Hazardous Locations/environmental Protection:

Pressure Switch - Page 1 of 2

Weathertight

Overall Length:

9.060 inches

Overall Height:

2.590 inches



View Online at https://aerobasegroup.com/nsn/5930-01-309-8644

Overall Width:
4.220 inches
Mounting Slot Width:
0.250 inches
Body Length:
4.220 inches
Distance Between Mounting Facility Centers:
2.750 inches
Pressure Switch Type:
Differential
Mounting Method:
Flange and slot
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Proof Pressure:
1000.00 pounds per square inch
Mounting Facility Pattern:
Mounting Facility Pattern: Two position in-line
• •
Two position in-line
Two position in-line Nonpile-up Contact Arrangement:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage Contact Adjustability:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +3.00/+50.00 actuation point pounds per square inch
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +3.00/+50.00 actuation point pounds per square inch Contact Adjustment Type:
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +3.00/+50.00 actuation point pounds per square inch Contact Adjustment Type: Internal actuation point shaft
Two position in-line Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary Terminal Type: Tab w/screw Contact Load Current Rating: 0.4 amperes resistive load second voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +3.00/+50.00 actuation point pounds per square inch Contact Adjustment Type: Internal actuation point shaft Contact Voltage Rating In Volts:

NSN 5930-01-309-8644

Pressure Switch - Page 2 of 2



Style	Designator
Recta	ngular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0