NSN 5930-01-310-5733

Pressure Switch - Page 1 of 2

Flared, threaded external single connection



View Online at https://aerobasegroup.com/nsn/5930-01-310-5733

Thread Class:
3a single pressure connection
Thread Length:
0.550 inches single pressure connection
Overall Length:
2.600 inches
Outside Diameter:
0.438 inches single connection
Body Length:
1.300 inches
Overall Diameter:
0.680 inches
Pressure Switch Type:
Gage
Width Across Flats:
0.680 inches
Operating Tempurature Rating:
Between -40.0 degrees fahrenheit and 120.0 degrees fahrenheit
Mounting Method:
Line
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Proof Pressure:
200.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
1.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
25.50 actuation point pounds per square inch gage and 15.50 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:

NSN 5930-01-310-5733Pressure Switch - Page 2 of 2



Media For Which Designed:
Liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0