

View Online at <https://aerobasegroup.com/nsn/5930-01-310-6076>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.125 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

**Overall Length:**

Between 0.960 inches and 0.995 inches

**Overall Height:**

Between 1.055 inches and 1.070 inches

**Overall Width:**

Between 0.865 inches and 0.875 inches

**First Flat Length:**

0.302 inches single actuator and 0.322 inches single actuator

**Flat Height:**

0.098 inches single actuator and 0.102 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.126 inches single actuator

**Shaft Length:**

0.390 inches single actuator and 0.410 inches single actuator

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3:00 o'clock

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical and coded

**Pole Quantity:**

1 single section periphery

**Throw Quantity:**

20 single section periphery

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

20 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes single section periphery

**Switch Actuator Positioning Increment:**

18.0 degrees single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level

**Contact Arrangement Truth Table:**

Special single section

**Special Truth Table Identification:**

37695-special 1-2-3-4-5-6 single section

**Precious Material And Location:**

Program disc surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Wafer, printed board, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0