

View Online at <https://aerobasegroup.com/nsn/5930-01-310-6076>

Thread Class:

2a single mounting facility

Thread Length:

0.125 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

Overall Length:

Between 0.960 inches and 0.995 inches

Overall Height:

Between 1.055 inches and 1.070 inches

Overall Width:

Between 0.865 inches and 0.875 inches

First Flat Length:

0.302 inches single actuator and 0.322 inches single actuator

Flat Height:

0.098 inches single actuator and 0.102 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.390 inches single actuator and 0.410 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and coded

Pole Quantity:

1 single section periphery

Throw Quantity:

20 single section periphery

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

20 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

18.0 degrees single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

Contact Arrangement Truth Table:

Special single section

Special Truth Table Identification:

37695-special 1-2-3-4-5-6 single section

Precious Material And Location:

Program disc surfaces gold

Precious Material:

Gold

Style Designator:

Wafer, printed board, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0