

View Online at <https://aerobasegroup.com/nsn/5930-01-310-6077>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.417 inches single mounting facility and 0.457 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

4.611 inches

**First Flat Length:**

0.230 inches single actuator and 0.270 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.417 inches single actuator and 0.457 inches single actuator

**Overall Diameter:**

Between 1.155 inches and 1.185 inches

**Individual Section Quantity:**

8

**Nonturn Device Type:**

Slotted bushing at 3:00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

12 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+1.000/+4.500 inch-pounds single actuator

**Contact Load Current Rating:**

1.3 amperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0