

View Online at <https://aerobasegroup.com/nsn/5930-01-310-6078>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

1.316 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.313 inches single actuator

Overall Diameter:

Between 1.172 inches and 1.328 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3:00 o'clock

End Application:

6625-01-125-3775 meter, impedance

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

0.5 amperes resistive load dc at sea level

Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions single section

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0