NSN 5930-01-310-6082

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-310-6082

Explosion proof

Overall Length:

6.290 inches

Overall Height:

1.800 inches

Overall Width:

1.725 inches

Unthreaded Mounting Hole Diameter:

1.000 inches single mounting facility

Individual Section Quantity:

11

Longest Horizontal Distance Between Mounting Centers:

6.114 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at altitude

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f each section

Contact Arrangement Truth Table:

Decimal, 1 pole - 16 positions each section

Color:

White 9th indicator background

Style Designator:

Rectangular inline indicating

Specification Data:

93322-7909179-500 manufacturers source control

NSN 5930-01-310-6082

Code Indicating Wheel Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0