NSN 5930-01-310-6084

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-310-6084 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Explosion proof and dustproof and moisture resistant and salt spray resistant **Overall Length:** Between 0.495 inches and 0.505 inches **Overall Height:** 1.212 inches **Overall Width:** 0.468 inches **Bushing Length:** 0.220 inches **Body Length:** Between 0.495 inches and 0.505 inches **Body Width:** 0.260 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Diameter:** Between 0.114 inches and 0.116 inches **Actuator Height:** 0.340 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position maintained **End Application:** Weapon system-aircraft, ac-130h, mc-130h, ec-130e, hc-130) **Mounting Surface To Terminal End Distance:** 0.652 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 40 **Thread Size:**

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

NSN 5930-01-310-6084 Toggle Switch - Page 2 of 2



Criticality Code Justification:	
Feat	
Special Features:	
Weapon system essential	
Precious Material And Location:	
Contact and terminal surface option gold and contacts and terminals silver	
Thread Series Designator:	
Uns	
Terminal Type And Quantity:	
3 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A053a0	