

View Online at <https://aerobasegroup.com/nsn/5930-01-310-6875>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.100 inches single mounting facility

**Overall Length:**

0.940 inches

**First Flat Length:**

0.312 inches single actuator

**Flat Height:**

0.100 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.368 inches single actuator

**Overall Diameter:**

0.540 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section front

**Throw Quantity:**

4 single section front

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

6.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts and rotor surfaces silver and common ring and terminal surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0