

View Online at <https://aerobasegroup.com/nsn/5930-01-310-6875>

Thread Class:

2a single mounting facility

Thread Length:

0.100 inches single mounting facility

Overall Length:

0.940 inches

First Flat Length:

0.312 inches single actuator

Flat Height:

0.100 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.368 inches single actuator

Overall Diameter:

0.540 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section front

Throw Quantity:

4 single section front

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts and rotor surfaces silver and common ring and terminal surfaces gold

Precious Material:

Silver and gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0