

View Online at <https://aerobasegroup.com/nsn/5930-01-310-8563>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

13.500 inches

Overall Height:

5.000 inches

Overall Width:

4.460 inches

Unthreaded Mounting Hole Diameter:

0.344 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

10.800 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate and cam actuated

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes inductive load highest ac voltage rating at sea level

Special Features:

Nameplate marking: hoist fast; hoist slow; off; lower slow; lower fast

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0