

View Online at <https://aerobasegroup.com/nsn/5930-01-310-9655>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Fungus resistant and salt spray proof

Overall Length:

3.490 inches

Outside Diameter:

0.438 inches single connection

Overall Diameter:

1.000 inches

Pressure Switch Type:

Gage

Width Across Flats:

Between 0.870 inches and 0.880 inches

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

6200.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

3000.00 actuation point pounds per square inch gage and 3100.00 actuation point pounds per square inch gage and 2700.00 deactuation point pounds per square inch gage and 2800.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0