

View Online at <https://aerobasegroup.com/nsn/5930-01-310-9655>

**Thread Class:**

3a single pressure connection

**Hazardous Locations/environmental Protection:**

Fungus resistant and salt spray proof

**Overall Length:**

3.490 inches

**Outside Diameter:**

0.438 inches single connection

**Overall Diameter:**

1.000 inches

**Pressure Switch Type:**

Gage

**Width Across Flats:**

Between 0.870 inches and 0.880 inches

**Mounting Method:**

Input port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

6200.00 pounds per square inch

**Thread Size:**

0.4375 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

2.0 amperes inductive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

3000.00 actuation point pounds per square inch gage and 3100.00 actuation point pounds per square inch gage and 2700.00 deactuation point pounds per square inch gage and 2800.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A048b0