

View Online at <https://aerobasegroup.com/nsn/5930-01-311-0613>

Body Style:

Surface mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 0.460 inches and 0.500 inches

Overall Height:

Between 0.380 inches and 0.480 inches

Overall Width:

Between 0.370 inches and 0.390 inches

Body Length:

Between 0.460 inches and 0.500 inches

Body Width:

Between 0.370 inches and 0.390 inches

Body Height:

Between 0.240 inches and 0.300 inches

Case Material:

Plastic

Switch Actuator Quantity:

4

Actuator Style:

Rectangular

Actuator Height:

0.080 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

24.0 dc

End Application:

1520-01-035-0266 helicopter, utility

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

4 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc

Test Data Document:

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 printed circuit

Specification Data:

81349-mil-s-83504/11 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0