

View Online at <https://aerobasegroup.com/nsn/5930-01-311-0613>

**Body Style:**

Surface mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 0.460 inches and 0.500 inches

**Overall Height:**

Between 0.380 inches and 0.480 inches

**Overall Width:**

Between 0.370 inches and 0.390 inches

**Body Length:**

Between 0.460 inches and 0.500 inches

**Body Width:**

Between 0.370 inches and 0.390 inches

**Body Height:**

Between 0.240 inches and 0.300 inches

**Case Material:**

Plastic

**Switch Actuator Quantity:**

4

**Actuator Style:**

Rectangular

**Actuator Height:**

0.080 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

24.0 dc

**End Application:**

1520-01-035-0266 helicopter, utility

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

4 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc

**Test Data Document:**

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 printed circuit

**Specification Data:**

81349-mil-s-83504/11 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0