

View Online at <https://aerobasegroup.com/nsn/5930-01-311-3685>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 1.940 inches and 2.060 inches

Outside Diameter:

0.125 inches single connection

Body Length:

Between 0.720 inches and 0.840 inches

Overall Diameter:

Between 0.820 inches and 0.940 inches

End Application:

3810-01-205-2716 crane, wheel mounted

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 150.0 degrees fahrenheit

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

300.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

3500.00 pounds per square inch gage

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

120.00 actuation point pounds per square inch and 50.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Swivel nut, flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0