

View Online at <https://aerobasegroup.com/nsn/5930-01-311-9936>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

1.309 inches

Overall Height:

0.625 inches

Overall Width:

0.625 inches

Body Diameter:

0.562 inches

Bushing Length:

0.297 inches

Body Length:

0.465 inches

Case Material:

Metal

Actuator Diameter:

0.375 inches

Actuator Height:

0.219 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

1520-01-020-4216 helicopter

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

U Inc

Terminal Type And Quantity:

2 tab w/screw

Specification Data:

81349-mil-s-8805/107 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0