NSN 5930-01-311-9938

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-311-9938
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof and moisture resistant
Overall Length:
0.750 inches
Overall Height:
3.060 inches
Overall Width:
0.750 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Body Height:
Between 1.380 inches and 1.450 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Red single actuator and red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes
inductive ac and 1.500 amperes lamp ac

Special Features: Vertical split lens

NSN 5930-01-311-9938

Push Switch - Page 2 of 2



Precious	Material	∆nd ∣	Location:

Contact surfaces gold and contacts silver

Terminal Type And Quantity:

18 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0