

View Online at <https://aerobasegroup.com/nsn/5930-01-312-1146>

Thread Class:

2a single pressure connection

Hazardous Locations/environmental Protection:

Watertight and oiltight

Overall Length:

3.812 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

6.500 inches

Overall Width:

3.219 inches

Body Height:

5.875 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

4.500 inches

End Application:

1905-01-154-1191 landing craft

Pressure Switch Type:

Gage

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

340.00 pounds per square inch

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.00/+140.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0