

View Online at <https://aerobasegroup.com/nsn/5930-01-312-1154>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.186 inches and 0.190 inches

**Body Length:**

0.510 inches

**Body Width:**

0.210 inches

**Body Height:**

0.350 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.086 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.057 inches and 0.067 inches

**Actuator Height:**

0.020 inches

**Actuator Free Position Height:**

0.340 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

4.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Mounting bracket provided part number 3018328

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0