NSN 5930-01-312-4640

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-312-4640

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.484 inches
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.578 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.725 inches
Actuator Roller Diameter:
0.188 inches
Actuator Roller Width:
0.125 inches
Maximum Voltage Rating In Volts:
125.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action single switch unit
Switch Actuating Force:
65.0 grams
Actuator Movement:
Between 0.109 pretravel inches and 0.030 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
0.100 amperes resistive ac
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:

NSN 5930-01-312-4640

Sensitive Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A053a0