NSN 5930-01-312-6726

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-312-6726

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight and watertight
Housing Height:
2.438 inches
Housing Length:
4.938 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.438 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.812 inches
Maximum Voltage Rating In Volts:
600.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, both positions maintained single switch unit
Switch Actuating Force:
192.0 inch-ounces
Actuator Movement:
6.5 pretravel degrees and 28.5 overtravel degrees and 4.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
1.500 amperes resistive dc and 5.000 amperes resistive ac
Special Features:
Serrated shaft, less actuator lever
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A053a0