

View Online at <https://aerobasegroup.com/nsn/5930-01-312-8177>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

1.340 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.100 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.378 inches single actuator

Overall Diameter:

0.688 inches

Individual Section Quantity:

4

End Application:

Uh-60 a/l

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

8.0 amperes resistive load dc at sea level

Special Features:

Secondary non procurable reference number b45-1-4-8n-d

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0