NSN 5930-01-313-0566

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-313-0566

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
2.906 inches
Overall Height:
7.906 inches
Overall Width:
2.375 inches
Body Height: 3.812 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Immersion well
Features Provided:
Electrical access port and tamper proof cap and manual reset button
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Screw
Screw Contact Load Current Rating:
Contact Load Current Rating:
Contact Load Current Rating: 10.0 amperes resistive load third voltage
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability:
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range:
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type:
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts:
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed:
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed: Gas or liquid
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed: Gas or liquid Style Designator:
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular Shelf Life:
Contact Load Current Rating: 10.0 amperes resistive load third voltage Contact Adjustability: Actuation point adjustable Contact Adjustment Range: +100.00/+225.00 actuation point degrees fahrenheit Contact Adjustment Type: Internal actuation point screw Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular Shelf Life: N/a

No

NSN 5930-01-313-0566

Thermostatic Switch - Page 2 of 2



Fiig:

A048b0