

View Online at <https://aerobasegroup.com/nsn/5930-01-313-2417>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight and waterproof and dustproof

Actuator Style:

Round

Actuator Diameter:

0.360 inches

Actuator Free Position Height:

1.406 inches

Housing Height:

1.630 inches

Housing Length:

3.700 inches

Housing Width:

1.570 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.310 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.190 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

32.1 ounces

Switch Actuating Force:

95.9 ounces

Actuator Movement:

Between 0.067 pretravel inches and 0.252 overtravel inches and 0.039 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.400 amperes resistive dc and 0.400 amperes inductive dc and 0.100 amperes lamp dc and 0.100 amperes motor dc and 1.000 amperes resistive ac and 1.500 amperes inductive ac and 0.500 amperes lamp ac and 0.500 amperes motor ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0