

View Online at <https://aerobasegroup.com/nsn/5930-01-313-2417>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Oiltight and waterproof and dustproof

**Actuator Style:**

Round

**Actuator Diameter:**

0.360 inches

**Actuator Free Position Height:**

1.406 inches

**Housing Height:**

1.630 inches

**Housing Length:**

3.700 inches

**Housing Width:**

1.570 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.310 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.190 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

32.1 ounces

**Switch Actuating Force:**

95.9 ounces

**Actuator Movement:**

Between 0.067 pretravel inches and 0.252 overtravel inches and 0.039 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

0.400 amperes resistive dc and 0.400 amperes inductive dc and 0.100 amperes lamp dc and 0.100 amperes motor dc and 1.000 amperes resistive ac and 1.500 amperes inductive ac and 0.500 amperes lamp ac and 0.500 amperes motor ac

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0