# NSN 5930-01-313-4098

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-313-4098
Inside Diameter:
0.500 inches single connection
Overall Length:
3.600 inches
Overall Height:
6.500 inches
Overall Width:
2.660 inches
Body Height:
3.310 inches
Unthreaded Mounting Hole Diameter:
0.280 inches
Longest Horizontal Distance Between Mounting Centers:
2.720 inches
Longest Vertical Distance Between Mounting Centers:
2.720 inches
End Application:
Used on main propulsion system onboard 180 ft wlb and various other coast guard vessels
Pressure Switch Type:
Gage
Operating Tempurature Rating:
185.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Decrease
Proof Pressure:
100.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:

Two position diagonal

### Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary

#### **Terminal Type:**

Tab w/screw

#### **Contact Load Current Rating:**

1.5 amperes resistive load third voltage

#### **Contact Adjustability:**

Actuation point adjustable, preset

## NSN 5930-01-313-4098

Pressure Switch - Page 2 of 2



## **Contact Adjustment Range:** +1.00/+75.00 actuation point pounds per square inch **Contact Adjustment Type:** External actuation point screw **Contact Stimulus Rating:** 10.00 actuation point pounds per square inch **Contact Voltage Rating In Volts:** 600.0 ac at sea level first voltage **Pressure Connector Type:** Plain, threaded internal single connection Media For Which Designed: Gas or liquid **Style Designator:** Rectangular **Thread Series Designator:** Npt single pressure connection Shelf Life: N/a **Unit Of Measure:**

**Demilitarization:** 

No Fiig: A048b0