## NSN 5930-01-313-6590

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-313-6590

Body Style:
Hole mounted
Actuator Length:
4.000 inches
Actuator Style:
Roller arm
Actuator Height:
0.745 inches
Actuator Roller Diameter:
1.250 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.100 inches
Housing Length:
4.950 inches
Housing Width:
2.310 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.220 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.810 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Base
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, double break, momentary action 3rd switch unit
Switch Actuating Force:
190.0 inch-ounces
Actuator Movement:
17.0 pretravel degrees and 63.0 overtravel degrees and 11.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
0.400 amperes resistive dc and 1.200 amperes resistive ac
Special Features:
High shock/corrosion treated
Precious Material And Location:
Contacts gold
Terminal Type And Quantity:
6 screw

## NSN 5930-01-313-6590

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0