## NSN 5930-01-313-8407

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-313-8407

**Thread Class:** 2a single mounting facility **Overall Length: 6.750** inches **Overall Height:** 3.000 inches **Overall Width:** 2.250 inches **Distance Between Mounting Facility Centers:** 2.312 inches single mounting facility **Individual Section Quantity:** 4 **Knob Manufacturer Code:** 65054 **Knob Manufacturer Part Number:** 310c624h01 **End Application:** Main propulsion control switchboard part number d-82-3008-3cg-01 onboard 180 ft wlb coast guard vessels **Switch Contact Basic Design:** Coded **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 20 single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 600.0 highest dc voltage rating at sea level **Mounting Facility Pattern:** Two position diagonal single mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Terminal Type:** Threaded stud **Contact Load Current Rating:** 20.0 amperes resistive load dc at sea level and 8.0 amperes resistive load dc at sea level **Contact Arrangement Truth Table:** Decimal, 1 pole - 8 positions each section **Style Designator:** Rectangular panel mount

Thread Series Designator: Unc single mounting facility

## NSN 5930-01-313-8407

Rotary Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0