

View Online at <https://aerobasegroup.com/nsn/5930-01-314-5595>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

0.385 inches

Bushing Length:

0.500 inches

Body Length:

1.300 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.148 inches and 0.158 inches

Actuator Height:

Between 0.124 inches and 0.164 inches

Actuator Free Position Height:

Between 0.624 inches and 0.664 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

2350-01-085-3792 carrier, personnel, full tracked

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

104.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 wire lead

Specification Data:

81349-mil-s-8805/73 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0