NSN 5930-01-314-6365

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-314-6365

| Hazardous Locations/environmental Protection: |
|--|
| |
| Explosion proof |
| Overall Length: |
| 6.060 inches |
| Overall Height: |
| 6.000 inches |
| Overall Width: |
| 7.500 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.530 inches single mounting facility |
| Distance Between Mounting Facility Centers: |
| 6.380 inches single mounting facility |
| Individual Section Quantity: |
| 1 |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Flange single mounting facility and unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob and legend plate and metallic inclosure |
| Contact Voltage Rating In Volts: |
| 440.0 highest ac voltage rating at sea level |
| Mounting Facility Pattern: |
| Two position in-line single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Terminal Type: |
| Tab w/screw |
| Switch Actuator Positioning Increment: |
| 45.0 degrees single actuator |
| Contact Load Current Rating: |
| 1.1 amperes inductive load lowest dc voltage rating at sea level |
| Special Features: |
| Legend plate reads: off, acknwldge |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

ı ııg.

A052b0