

View Online at <https://aerobasegroup.com/nsn/5930-01-314-6373>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight

Actuator Style:

Round

Actuator Diameter:

0.312 inches

Actuator Free Position Height:

0.828 inches

Housing Height:

1.531 inches

Housing Length:

3.094 inches

Housing Width:

1.562 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.469 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

24

Thread Size:

0.190 inches

Nonpile-up Contact Arrangement:

1 two circuit, one position momentary single switch unit

Switch Actuating Force:

40.0 ounces

Actuator Movement:

0.115 pretravel inches and 0.115 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

110.000 milliamperes resistive dc and 110.000 milliamperes inductive dc and 10.000 amperes resistive ac and 1.200 amperes inductive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0