

View Online at <https://aerobasegroup.com/nsn/5930-01-314-6373>

**Thread Class:**

2b

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Oiltight

**Actuator Style:**

Round

**Actuator Diameter:**

0.312 inches

**Actuator Free Position Height:**

0.828 inches

**Housing Height:**

1.531 inches

**Housing Length:**

3.094 inches

**Housing Width:**

1.562 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.469 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.156 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 240.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.190 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, one position momentary single switch unit

**Switch Actuating Force:**

40.0 ounces

**Actuator Movement:**

0.115 pretravel inches and 0.115 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

110.000 milliamperes resistive dc and 110.000 milliamperes inductive dc and 10.000 amperes resistive ac and 1.200 amperes inductive ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0